

Checklist | F-Bag Replacement

BEFORE

1. **PROTECTIVE GLOVES** | To be worn during replacement procedure
2. **REPLACEMENT G-Bag** | Prepare before disconnecting full F-Bag
3. **TAPS & SINKS** | Ensure all are turned off and drained



Protect
from Sharp
Objects

DURING

4. **DISPLACE EXCESS WATER** | Remove lid and gently push down on F-Bag to remove excess water
5. **COUPLERS** | Undo clips and gently slide away from F-Bag
6. **G-Bag INLET & OUTLET** | Wipe inside of F-Bag inlet & outlet pipe ensuring a secure fit for the stoppers.
7. **STOPPERS** | Insert to seal the F-Bag to avoiding spillage during removal
8. **G-Bag** | Remove for secure storage and disposal
9. **REPLACE G-Bag** | Fit new F-Bag and reconnect the rubber coupler (**Don't over tighten clips**)

AFTER

10. **REFILL G-Bag** | Run the tap to restore water level
11. **CHECK** | Water is running freely to expand the F-Bag to fill casing
12. **REPLACE LID** | To protect the F-Bag

More info?
Scan to watch
Or visit www.goodflo.com
for maintenance video



Need a biological solution to breakdown denser fats, oils and grease? To supplement your grease trap why not consider...



Grease Dose Premium



Scan to place order



Or call us on 01926 334 466